



P640: Card Printer

The Ultimate in Secure ID Card Printing



Ideal for:

- » Drivers Licenses
- » Government & Military ID Cards
- » High Security Access Control ID Cards
- » Law Enforcement and Correctional Facility ID Cards
- » Airport ID Cards
- » Applications requiring long lasting, secure issuance of tamper-evident ID's

For high volume, high security applications, choose the Zebra P640i dual-sided laminating printer. Zebra's industry-leading security printers are used in over 50 countries to print tens of millions of ID cards annually. The P640i 's dual-sided printing and "one pass" dual-sided lamination provide the maximum amount of flexibility in protecting driver's licenses, national voter registration cards, and other types of secure IDs. With its high throughput, superior print quality and best total cost of ownership in its class, the P640i is the right choice for issuing durable and highly secure ID cards.

High Card Issuance Security

- » Flexible features & options to secure your entire card issuance process
- » Optional ID/Key prevents unauthorized printer use
- » ID/Log driver utility builds a customizable card transactions record in the printer's host computer for added security

High Performance

- » Unique card transport with stable card movement across printhead for superior image quality
- » Fast laminating and printing speed combine to deliver maximum card throughput per hour

Industry Leading Cost Savings

- » Best total cost of ownership in its class
- » Patented linerless lamination dramatically reduces the cost of laminate material and is waste-free
- » High capacity supplies save operator time reloading media

Built for Maximum Productivity

- » Consistent, reliable operation, high print speed and minimal operator attention provide maximum card output over years of intense use
- » Weight saving design makes the P640*i* easier to transport
- » Translucent covers allow you to see when supplies are running low

Flexible Options to Increase Card Security

- » Optional built-in 10/100 Ethernet connectivity simplifies printer networking and enables distributed printing across sites
- » Magnetic stripe encoding
- » Smart card encoding capabilities
- » Linear barcode scanner

P640*i*

Card Printer Product Specifications



General Specifications	Laminate Specifications**
» Dual-sided color printing	» Linerless & waste-free 1.0 mil laminate, 600 cards/roll
 One-pass dual-sided lamination (waste-free) 	» 2 Laminate cassettes (upper & lower)
Micro-positioning card transport system for enhanced color photos	» Laminates available:
Covert text printing capability (approx. 17 mil high)	Clear full size, clear for magnetic stripe cards, and clear for smart cards. Custor
Automated card cleaning before printing	laminates available upon request:
Windows $^{\scriptscriptstyle \otimes}$ drivers for 2000 and XP with advanced security features (ID/Log &	Holographic images
password protection)	UV images
One year printer warranty	**for optimum laminator performance use Genuine Zebra Supplies.
One year (unlimited passes) printhead warranty	
	Communications Interface
Printing	» USB 1.1 (Standard, USB 2.0 compatible)
Color dye sublimation and resin K	» Factory Installed Options
120 cards per hour dual-sided printing and laminating (YMCK ribbon	Built-In 10/100 Ethernet
& 1.0 mil laminate both sides)	Bi-directional Parallel with ECP support (minimum order required)
300 dpi (11.8 dots/mm) print resolution	
	Mechanical
Bar Codes	» Width: 27.5 in (699 mm) not including exit hopper
» Bar codes and other symbologies available via Windows driver	» Depth: 9.7 in (246 mm)
	» Height: 11.5 in (292 mm)
Fonts	» Weight: 35 lbs (15.9 kg)
True Type or other type fonts via Windows driver	 Electrical
Cord Crestifications*	» 110 - 220 Volts AC, 50/60 Hz
Card Specifications*	- » FCC Class A, UL, CUL, & CE approved
• Types: PVC Composite	
Card width/length: ISO CR-80 - ISO 7810 2.12" (54mm) x 3.38" (86mm)	Environmental
HiCo Magnetic Stripe - ISO 7811	» Operating temperature: 50°F to 95°F (10°C to 35°C)
Contact Smart Card - ISO 7816 Compliant	» Operation humidity: 20% to 80% non-condensing
Contactless Smart Card - MIFARE®/DESFire	» Storage temperature: -4°F to 158°F (-20°C to 70°C)
o Card thickness: 27 mil - 33 mil	» Storage humidity: 5% to 90% non-condensing
» Card input hopper capacity: 150 cards	» Ventilation: Free air
Ribbon Specifications*	_ Options
YMCK: 600 cards/roll	» ID/Key security printing feature
» YMCKK: 500 cards/roll	» Magnetic encoder, 3 track (30 mil cards only, HiCo only)
» YMCUvK: 500 cards/roll	» Smart card MIFARE [®] /DESFire encoder/reader
Monochrome black: 3000 images/roll	» Smart card contact station
Other monochrome colors available	» Smart card contact-ISO 7816 encoder/reader
» Cleaning cartridge: cleans 3,000+ cards	» Built-in Ethernet for networking capability

*for optimum printer performance use Genuine Zebra Supplies

www.zebracard.com



An ISO 9001 registered company ©2005 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infrigement is made for or implied by the use thereof. Part No. P640i-06/07

North America

Zebra Technologies Corporation

Card Printer Solutions 1001 Flynn Road Camarillo, CA 93012-8706 USA Telephone: +1 805 579 1800

Fax: +1 805 579 1800 Fax: +1 805 579 1808 Toll free in US: 800 452 4056 e-mail: cards@zebra.com

Europe, Middle East, Africa

» Linear barcode scanner
 » Warranty programs

Zebra Technologies Corporation Card Printer Solutions The Valley Centre, Gordon Road High Wycombe Buckinghamshire HP13 6EQ, UK Telephone: +44 870 241 1527 Fax: +44 870 241 0765 e-mail: eurosales@zebra.com

Asia Pacific

Zebra Technologies Corporation Card Printer Solutions 120 Robinson Road #06-01 Parakou Building Singapore 068913 Telephone: +65 6858 0722 Fax: +65 6885 0836 e-mail: asiasales@zebra.com

Latin America

Zebra Technologies Corporation Card Printer Solutions 9800 NW 41st Street, Suite 220 Doral, FL 33178 USA Telephone: +1 305 558 3100 Fax: +1 305 558 8485 e-mail: latinsales@zebra.com

RoH