



P430i Card Printer



Performance, Reliability,
and Expandability in a
Dual-sided Card Printer

The Zebra P430i is part of the latest generation of Zebra's most popular card printer family, with tens of thousands of printers installed worldwide. Designed and built for demanding environments, the P430i delivers reliability and performance for high-volume card production. Expansion options for networking and card encoding give the P430i the flexibility to meet your specific requirements. Affordable and easy to use, the Zebra P430i is the new leader in dual-sided performance card printers.



Ideal for:

- » Employee ID cards
- » Student and faculty ID cards
- » Access control cards
- » Personalised membership and loyalty cards
- » Gift cards
- » Visitor ID cards
- » Government Licences

Innovative and Easy-to-Use

- » Easy plug and play USB or USB with Ethernet interface simplifies configuration
- » Printhead bracket opens wide for easy ribbon access
- » 16 character LCD screen for printer status and error reporting messages
- » Translucent card cover allows you to see when supplies are running low, and blank cards can be added while printing
- » Reject bin holds cards that fail to encode correctly

Encoding and Network Connectivity Expansion Options

- » 3 track magnetic stripe encoding (HiCo/LoCo)
- » Contact and contactless smart card encoding capabilities
- » Built-in 10/100 Ethernet for printer networking simplifies device management and eliminates the need for third party external device.

Reliable and Flexible

- » Print dual-sided or single-sided
- » Revolutionary angled card feeder design means fewer rejected cards*
- » Self-aligning printhead design for consistently uniform print quality

High Performance

- » Vibrant, true-to-life colours
- » High volume card throughput
- » Large capacity card feeder available

i Series* Functionality

- » Automatic colour optimisation and driver configuration
- » Enhanced ribbon formulation for optimal colour output
- » Ribbon image counter and ribbon low notification

*Patent pending



www.alphacard.com
1-800-717-8080

P430i



Card Printer Product Specifications

General Specifications

- » 16-character LCD display
- » Windows® drivers for 2000 and XP; Vista compatible
- » Bi-directional driver communication
- » Two year printer warranty
- » Two year (unlimited passes) printhead warranty

Printing

- » Colour dye sublimation or monochrome thermal transfer printing
- » 102 cards per hour full colour dual-sided (YMCKOK)
- » 130 cards per hour full colour single-sided (YMCKO)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Card Specifications

- » Types: PVC, PVC Composite, Adhesive backed
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Smart Card contact and contactless
- » Card thickness: 10 mil (.25mm) to 60 mil (1.524mm) (+/- 10%)
- » Card feeder capacity: 100 cards (30 mil) or 220 cards (30 mil)
- » Card output hopper capacity: 100 cards (30 mil)

Communications Interface

- » USB 1.1 (USB 2.0 compatible) cable included
- » Optional Built-in 10/100 Mbps Ethernet



Software drivers for the Zebra P430i Card Printer have been tested to ensure that they meet Microsoft® standards for Windows® compatibility. Microsoft, Windows, and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

Ribbon Specifications*

- » i Series™ Printers require the use of i Series ribbons for full colour printing
- » YMCKOK: 170 cards/roll
- » YMCKO: 200 & 330 cards/roll
- » 1/2 Panel YMC Full KO: 450 cards/roll
- » KdO: 500 cards/roll
- » KrO: 500 cards/roll
- » Overlay varnishes: Clear and Hologram: 350 cards/roll
- » Monochrome: 1500 (Black) & 1000 cards/roll
- » Monochrome colours: black, red, blue, green, silver, gold, white and scratch-off grey



*for optimum printer performance use Genuine Zebra Supplies

Mechanical

- » Width: 26 in (660 mm)
- » Depth: 9.4 in (239 mm)
- » Height: 10.1 in (256 mm)
- » Weight: 20 lbs (9.1 kg)

Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » 4MB image memory standard
- » FCC Class A, CE, UL, CUL, and CCC approved

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Built-in 10/100 Mbps Ethernet
- » Smart card contact-ISO 7816 encoder (30 mil cards only)
- » Smart card MIFARE®/DESFire and HID iClass® encoder (30 mil cards only)
- » Magnetic encoder (30 mil cards only) 3 track HiCo/LoCo
- » High capacity feeder (220 cards)
- » Cleaning supplies

Genuine Zebra Supplies

- » Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Zebra Supplies meet stringent quality standards and are tested for optimum performance with Zebra card printers.

www.zebracard.com



Zebra Technologies Corporation



An ISO 9001 registered company ©2005 ZIH Corp.
Specifications listed are for base model printers with standard features only unless otherwise noted. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof. **Part No. P430i-05/06**

North America

Zebra Technologies Corporation
Card Printer Solutions
1001 Flynn Road
Camarillo, CA 93012-8706
USA
Telephone: +1 805 579 1800
Fax: +1 805 579 1808
Toll free in US: 800 452 4056
e-mail: cards@zebra.com

Europe, Middle East, Africa

Zebra Technologies Corporation
Card Printer Solutions
The Valley Centre, Gordon Road
High Wycombe
Buckinghamshire HP13 6EQ, UK
Telephone: +44 870 241 1527
Fax: +44 870 241 0765
e-mail: eurosales@zebra.com

Asia Pacific

Zebra Technologies Corporation
Card Printer Solutions
16 New Industrial Road
#05-03 Hudson TechnoCentre
Singapore 536204
Telephone: +65 6858 0722
Fax: +65 6885 0836
e-mail: asiasales@zebra.com

Latin America

Zebra Technologies Corporation
Card Printer Solutions
9800 NW 41st Street, Suite 220
Doral, FL 33178
USA
Telephone: +1 305 558 3100
Fax: +1 305 558 8485
e-mail: latinsales@zebra.com